

Bearings NO.	d	D	B	C	Cr	C0r	Weight
	mm	mm	mm	mm	kN	kN	kg
319148 B	105	150	71	71	255	475	4.1
BC4B 319768	125	180	100	90	429	880	7.9
315643/VJ202	127	174.625	150.812	150.812	627	1320	10.5
BC4B 459696	139.7	215	195	187	1210	2550	24
314625	145	210	155	155	792	1560	18
313924 A	145	225	156	156	897	1660	23
313891 A	150	230	156	156	897	1660	24
314024 C	151.5	230	168	168	1050	2200	24
314190	160	230	130	130	781	1340	17
315189 A	160	230	168	168	897	2200	23.5
315642/VJ202	165.1	225.425	168.275	168.275	1100	2240	20
BC2B 322340/HB1VJ202	170	230	160	160	1100	2360	19
BC4B 635122	170	240	130	130	913	1830	19
313812	180	260	168	168	1280	2500	29.5
BC4B 452683 A	181	260	180	180	968	2600	28
314023 A	181.5	260	168	168	1120	2550	27.5
312942	182	260	183	168	1140	2600	28
313651	190	260	168	168	1140	2600	27
314199 B	190	270	200	200	1510	3350	37.5
313583	190	280	200	200	1510	3350	40
314049 A	190	280	200	200	1720	3350	41.5
313153	192	270	170	170	1170	2700	28.5
314553	200	270	170	170	1170	2700	28.5
314385	200	280	170	170	1380	3000	33.5
313893	200	280	200	200	1510	3350	39
313811	200	290	192	192	1540	3200	42.5
313639 A/VJ202	200	310	230	230	2010	3750	63
313584 K	205	310	225	225	1940	4300	58
313839	220	310	192	192	1680	3650	46
313894 B	220	310	225	225	1940	4300	54.5
314889/VJ202	220	330	230	230	2050	4000	68.5
313824	230	330	206	206	1870	4000	58
312943 C	231	330	235	220	1720	4300	59
313921	240	330	220	220	1720	4300	58
313823	260	370	220	220	2160	4650	77.5
313427 B	260	400	290	290	3520	7100	135
BC4B 457929 VCA	266.25	400	285	285	2550	6800	120
313822	280	390	220	220	2240	5000	82.5
314719 C	280	390	275	275	3080	7200	100
314070/VJ202	280	400	285	285	3140	7350	120
314897/VJ202	280	410	300	300	3520	7500	130
NNUD 6056 MAS	280	420	250	250	3190	6800	125
314484 D	300	420	300	300	3740	8800	130
319129	300	420	320	300	3740	8800	135
BC4B 322216 B/HA3VJ212	320	460	240	240	2920	7200	140
314274 B	320	480	350	350	4950	10800	220
BC4B 316345 A	320	480	350	350	4570	11000	215
313445 C	330	460	340	340	4180	10200	175
BC4-8050	340	450	250	250	2550	6000	115
314485 C	340	480	350	350	4750	11000	205
319040 A	340	480	370	350	4570	11000	200
BC4B 322261/HB1	340	500	370	370	5230	11800	260
315767 K	340	520	300	300	4290	9000	215
313404 A	340	560	380	380	6820	12900	350

Bearings NO.	d	D	B	C	Cr	C0r	Weight
	mm	mm	mm	mm	kN	kN	kg
314563/VJ202	350	500	380	380	4950	11400	240
BC4B 322777/HB1	350	500	410	410	5830	13700	285
BC2B 319878/VJ202	350	520	300	300	4290	9000	220
BC4B 326909/HA3	350	520	300	300	4290	9000	220
BC4-8022/HA1	355.6	482.6	269.87	269.87	2970	6400	150
BC4B 457939 VAA	356.67	550	400	400	5280	15000	335
BC2B 320075/VJ202	360	500	250	250	3580	7350	145
BC2B 322217/VJ202	360	500	250	250	3470	8500	140
316890 B	360	510	400	380	5230	12200	260
NNUD 6072 MA/P64	360	540	325	335	4680	9150	260
313041 C	365	540	300	300	5010	11000	230
314486 A	370	520	380	380	5500	13200	255
NNU 4976 B/DRW33	380	520	280	280	2860	7200	185
BC2B 326131/HB1VJ202	380	540	260	260	3410	8650	205
313030 A	380	540	300	300	5010	11000	220
315606	380	540	400	380	5720	13700	295
BC4B 313511 B	380	540	400	400	5720	13700	295
BC4B 320989/HA3	380	540	400	380	6050	14000	300
BC4B 326366/HB1	380	540	400	400	6160	15000	305
BC4B 322189	380	560	300	300	4950	9650	260
BC4B 322264/HB1	380	560	325	325	5230	10600	265
NNUD 6076 M	380	560	325	325	4840	10000	265
319352	382.5	590	450	450	6930	16300	425
BC4B 322498	390	540	320	320	5280	12200	230
313190 A	390	550	310	310	5120	11200	240
313038 A	399.93	590	440	440	8580	20400	420
BC4-8059	400	560	300	300	4680	10200	245
313015 DC	400	560	410	410	6270	15600	315
315802/VJ202	400	590	440	440	7370	16600	415
316689	410	560	400	400	6440	16000	290
BC4B 322038/HA2	410	560	400	400	5500	16000	295
BC4B 320612	410	560	420	400	5940	14600	275
313877 B	410	600	440	440	7650	17300	425
314964	412.335	650	488	488	8420	19000	575
BC4B 467373 VCA	412.335	650	488	480	7480	21200	565
BC4B 457945 VCA	412.5	630	450	450	6600	19000	490
BC2B 320074 A/VJ202	420	580	260	260	4400	9650	210
BC2B 326137/HB2VJ202	420	580	260	260	4730	10600	215
313555 B/VJ202	420	580	320	320	4680	10800	250
313555 C/VJ202	420	580	320	320	4680	10800	250
313513	420	600	440	440	7210	17600	400
314391/VJ202	420	620	400	400	6930	15600	430
BC4B 326361 B/HA1	431.5	571.5	300	300	4460	10200	210
BC4-8037/HA1VA907	431.8	571.5	310	310	4460	10200	200
314554 B	440	620	450	450	7810	19600	440
BC4B 320608	440	620	470	450	7210	17600	420
313032	440	650	355	355	6270	14600	400
316899 A	440	650	355	355	6710	14000	420
635043	440	660	340	340	6710	13700	430
314792 A	447.295	635.176	463.55	463.55	8250	20000	460
315811 E	450	590	300	300	3910	12000	245
312980 D	459.95	760	600	600	14000	30500	1160
313031 A	460	650	355	355	6270	14600	380
315196 A	460	650	424	424	7810	18300	450

Bearings NO.	d	D	B	C	Cr	C0r	Weight
	mm	mm	mm	mm	kN	kN	kg
BC4B 322993 A/HA7	460	650	460	424	7810	18300	490
314560	460	650	470	470	8800	22400	510
319155	460	650	470	470	8800	22400	520
BC4B 322374	460	680	400	400	8090	17300	640
BC4-8000/HA1	474.6	600	368	368	5500	14600	235
BC4-8031/HA1VA907	474.6	600	377	377	5500	14600	235
BC4-8004/HA1VA907	475	600	368	368	5120	13400	225
BC4B 326261/HA1	475	600	368	368	5500	14600	235
BC4-8003/HA1VA907	475	600	392	392	5500	14600	240
316690 B	480	650	450	450	8250	21200	440
319320	480	680	420	420	8420	19300	515
313516 D	480	680	500	500	9520	24000	585
316624	480	680	500	500	9130	22000	605
315523	485	740	540	540	11000	28500	830
BC2B 326196/HA1VJ202	487.98	637.045	350	350	5940	15300	300
319254/VJ202	500	650	260	260	4020	10200	225
316083 A	500	670	450	450	8250	22000	460
BC4-8010/HA4	500	670	479	450	8250	22000	485
BC4B 322039/HA1	500	670	480	450	8250	22000	485
BC4-8051/HA	500	670	480.5	450	8250	22000	465
BC4-8011/HA4	500	670	517	450	8250	22000	475
BC4-8052/HA	500	670	518.5	450	8250	22000	475
BC4B 316515	500	680	450	450	8250	22000	500
316968 A	500	710	480	480	8800	21600	610
BC4B 322066	500	720	400	400	7920	17600	530
314441 B	500	720	530	530	10800	28500	730
BC4B 326853/HB1	500	738	500	500	10800	23200	735
BC4B 319411	510	680	500	500	8970	26000	522
BC4-8009/HB1	510	730	520	520	9520	22000	750
BC4-8007/HB1	510	760	550	550	12100	26500	950
BC4B 457956 VCE	511.584	780	580	580	11900	34700	915
312844/VJ202	529.91	870	670	670	15700	33500	1660
314886 A	530	760	520	520	11700	28500	775
315040/VJ202	530	780	500	500	9350	20400	805
314517 A	530	780	570	570	12800	32500	960
313535 B	536.176	762.03	558.8	558.8	11400	29000	830
313535 D	536.176	762.03	558.8	558.8	11400	29000	840
BC4B 322142/HB1	536.176	762.03	558.8	558.8	11200	30000	820
316691	550	740	510	510	10100	27000	615
316115/VJ202	550	800	520	520	11700	26500	895
BC4B 322719/HB1	550	800	560	560	12100	28000	930
BC4B 457960 VCA	551.667	830	580	580	12300	32500	1070
BC4-8046/HB1	556	800	580	580	10500	25500	900
313189 A	559.84	920	710	710	20100	45500	2000
BC4B 322930/HA4	560	820	600	600	14200	34000	1080
313499 B	571.1	812.97	594	594	13400	33500	1000
313499 DA	571.1	812.97	594	594	13400	33500	1000
BC4B 319446	571.627	870	640	640	13400	40500	1335
BC4B 457962 VCA	571.667	870	640	640	17900	50000	1170
BC4-8012/HA4	580	780	520	486	9900	27000	700
BC4B 326140/HA4	580	780	521	486	9900	27000	700
BC4-8053/HA4	580	780	521.5	486	9900	27500	700
BC4-8013/HA4	580	780	558	486	9900	27000	715
BC4-8054/HA4	580	780	559.5	486	9900	27500	715

Bearings NO.	d	D	B	C	Cr	C0r	Weight
	mm	mm	mm	mm	kN	kN	kg
315175 A	600	820	575	575	13000	36000	910
315175 C	600	820	575	575	13000	36000	935
315068 A	600	870	540	540	13200	31500	1100
BC4B 322497/HA4	600	870	578	540	13200	31500	1150
314317 A	600	870	640	640	15100	40000	1300
315513	600	870	640	640	15700	40000	1340
315526	606.667	920	640	640	16500	45000	1525
315257 A	610	820	430	430	9350	23600	650
BC4-8041/HA4	620	820	475	475	10100	26500	700
315071 A	628	922	600	600	16500	39000	1420
BC2-8012/HB1VJ202	630	850	436	436	7480	23600	720
BC4B 457969	633.334	960	680	680	14500	45000	1675
313705 B	634.5	901.87	674	674	16800	45000	1400
BC4-8002/HA6	650	900	650	650	17200	41500	1260
313007 C	650	920	670	670	17200	46500	1450
BC4B 320525	658	1075	650	650	20500	43000	2490
239509 FA	660	820	440	440	7480	22800	530
313477 B/VJ202	660	880	450	450	7210	23600	785
313154 C	680	980	640	640	17200	44000	1590
313008 A	690	980	715	715	19800	54000	1780
316967	700	930	620	620	15100	43000	1180
313403 C	710	1000	715	715	20100	56000	1860
315982	730	960	620	620	15400	45000	1220
314518 B	730	1030	750	750	20900	58500	2040
BC4B 420625	748	1135	690	690	22000	51000	2635
314420/VJ202	750	1000	500	500	12300	33500	1150
315973	750	1000	670	670	17600	50000	1480
NNUD 60/750 M	750	1090	615	615	18300	41500	1860
BC4-8066/HA3	750	1090	750	750	21600	51000	2420
313685 A	759	1210	740	740	27000	63000	3500
313685 B	759	1210	740	740	25500	85000	3480
312979 D	760	1080	790	790	23800	65500	2440
312967 E	761.425	1079.602	787.4	787.4	23800	65500	2400
BC4B 322143/HB3	761.425	1079.602	787.4	787.4	23300	65500	2410
BC4B 319991/HA4	773.334	1120	800	800	23800	65500	2715
BC4-8015/HB1	780	1070	780	780	22400	61000	2300
315599 A	800	1080	700	700	19800	58500	1950
BC4B 457984 VCA	811.692	1180	850	850	25100	68000	2980
BC4B 316341/HA4	820	1100	745	720	19800	57000	2000
BC4-8014/HA4	820	1130	800	800	24200	68000	2540
BC4B 320455	820	1130	800	800	24200	68000	2540
319313	820	1130	825	800	24200	68000	2570
315826 A	850	1150	840	840	25500	75000	2570
315826 B	850	1150	840	840	25500	75000	2660
BC4-8021/HB1	850	1180	850	850	26000	73500	2900
312966 D	862.98	1219.302	876.3	889	30300	86500	3470
312966 E	862.98	1219.302	876.3	889	30300	86500	3470
BC4B 319668	865	1180	750	750	23300	67000	2520
316043	900	1220	840	840	26400	80000	3060
BC4-8067/HA3	900	1280	780	780	28600	64000	3280
313528 C	900	1280	930	930	33000	93000	4080
BC4B 457995 VCA	918.354	1330	950.125	950	26400	85000	4380
315265	937.5	1270.25	825.5	825.5	28100	83000	3160
BC4B 319862	950	1360	975	975	34100	100000	4900

Bearings NO.	d	D	B	C	Cr	C0r	Weight
	mm	mm	mm	mm	kN	kN	kg
314520 C	950	1360	1000	1000	38000	110000	5020
314520 CK30	950	1360	1000	1000	38000	110000	4830
319303	980	1310	880	880	28600	86500	3310
316234 A	1000	1360	800	800	27500	83000	3560
BC4-8062/HA1	1040	1440	1000	1000	38000	93000	5100
315494 B	1200	1590	1050	1050	41800	134000	5970
BC4-8016/HA4	1300	1655	890	880	37400	122000	4800
BC4-8029/HA4	1350	1765	1360	1360	40200	122000	9100
BC4-8042/HA4	1400	1780	1200	1200	52300	163000	7400
BC4-8005/HA4	1400	1900	1360	1360	61600	183000	11300

