

Bearings NO.	d	D	B	Cr	Cor	Limiting speed	weight
	mm	mm	mm	kN	kN	rpm	kg
SL183004	20	42	16	27.5	26.5	9000	0.11
SL182204	20	47	18	41	37.5	7000	0.16
SL183005	25	47	16	31.5	32.5	7500	0.12
SL182205	25	52	18	46	45	6000	0.18
SL192305	25	62	24	63	57	4500	0.37
SL183006	30	55	19	40.5	43	6500	0.2
SL182206	30	62	20	61	63	5000	0.3
SL192306	30	72	27	87	85	3800	0.56
SL183007	35	62	20	49.5	55	5500	0.26
SL182207	35	72	23	76	77	4300	0.44
SL192307	35	80	31	113	112	3400	0.74
SL183008	40	68	21	59	68	5000	0.31
SL182208	40	80	23	84	89	3800	0.55
SL192308	40	90	33	152	155	3000	1.01
SL183009	45	75	23	63	76	4600	0.4
SL182209	45	85	23	88	96	3600	0.59
SL192309	45	100	36	162	165	2700	1.37
SL183010	50	80	23	77	92	4300	0.43
SL182210	50	90	23	95	109	3300	0.64
SL192310	50	110	40	205	215	2500	1.81
SL183011	55	90	26	105	134	3700	0.64
SL182211	55	100	25	122	145	3000	0.87
SL192311	55	120	43	242	255	2300	2.28
SL182912	60	85	16	54	74	3800	0.29
SL183012	60	95	26	108	141	3500	0.69
SL182212	60	110	28	152	179	2700	1.18
SL192312	60	130	46	260	280	2100	2.88
SL182913	65	90	16	57	81	3500	0.31
SL183013	65	100	26	113	154	3200	0.73
SL182213	65	120	31	177	213	2500	1.57
SL192313	65	140	48	315	355	1900	3.52
SL182914	70	100	19	76	108	3200	0.49
SL183014	70	110	30	134	171	3100	1.02
SL182214	70	125	31	183	226	2400	1.66
SL192314	70	150	51	345	390	1800	4.33
SL182915	75	105	19	78	116	3000	0.52
SL183015	75	115	30	141	188	2800	1.06
SL182215	75	130	31	190	239	2300	1.75
SL192315	75	160	55	410	475	1700	5.3
SL182916	80	110	19	81	123	2900	0.55
SL183016	80	125	34	173	224	2600	1.43
SL182216	80	140	33	223	280	2100	2.15
SL192316	80	170	58	480	560	1600	6.32
SL182917	85	120	22	102	155	2700	0.81
SL183017	85	130	34	178	235	2500	1.51
SL182217	85	150	36	255	320	2000	2.74
SL192317	85	180	60	510	620	1500	7.34
SL182918	90	125	22	106	165	2500	0.84
SL183018	90	140	37	207	280	2300	1.97
SL182218	90	160	40	285	365	1900	3.48
SL192318	90	190	64	560	660	1400	8.83
SL182919	95	130	22	114	172	2400	0.86
SL182219	95	170	43	335	430	1700	4.17
SL192319	95	200	67	580	720	1350	10.2

Bearings NO.	d	D	B	Cr	Cor	Limiting speed	weight
	mm	mm	mm	kN	kN	rpm	kg
SL182920	100	140	24	132	199	2300	1.14
SL183020	100	150	37	218	305	2200	2.15
SL182220	100	180	46	390	520	1600	5.13
SL192320	100	215	73	710	860	1300	13
SL182922	110	150	24	137	213	2100	1.23
SL183022	110	170	45	285	395	2000	3.5
SL182222	110	200	53	455	590	1500	7.24
SL192322	110	240	80	840	970	1150	17
SL182924	120	165	27	176	285	1900	1.73
SL183024	120	180	46	300	435	1800	3.8
SL182224	120	215	58	530	730	1400	9.08
SL192324	120	260	86	990	1220	1050	22.3
SL182926	130	180	30	210	350	1800	2.33
SL183026	130	200	52	430	610	1700	5.65
SL182226	130	230	64	630	860	1300	11.25
SL182928	140	190	30	228	375	1600	2.42
SL183028	140	210	53	455	670	1500	6.04
SL182228	140	250	68	720	1020	1200	14.17
SL182930	150	210	36	455	670	1500	3.77
SL183030	150	225	56	475	700	1500	7.33
SL182230	150	270	73	830	1180	1100	18.43
SL182932	160	220	36	320	520	1400	4
SL183032	160	240	60	540	810	1400	8.8
SL182232	160	290	80	1020	1460	1000	23
SL182934	170	230	36	330	560	1300	4.3
SL183034	170	260	67	710	1070	1300	12.2
SL182234	170	310	86	1140	1660	950	28.65
SL182936	180	250	42	410	690	1300	6.2
SL183036	180	280	74	820	1260	1200	16.1
SL182236	180	320	86	1180	1760	900	29.8
SL182938	190	260	42	455	790	1200	6.5
SL183038	190	290	75	840	1320	1100	17
SL182238	190	340	92	1300	1900	850	35.65
SL181840	200	250	24	178	320	1200	2.57
SL182940	200	280	48	550	940	1100	9.1
SL183040	200	310	82	960	1530	1100	21.8
SL182240	200	360	98	1420	2040	850	43.12
SL181844	220	270	24	187	350	1100	2.8
SL182944	220	300	48	570	1040	1000	9.9
SL183044	220	340	90	1150	1810	1000	28.4
SL181848	240	300	28	212	405	1000	4.4
SL182948	240	320	48	600	1130	950	10.6
SL183048	240	360	92	1210	1990	900	30.9
SL181852	260	320	28	222	440	950	4.71
SL182952	260	360	60	790	1460	900	18.5
SL183052	260	400	104	1620	2550	800	44.5
SL181856	280	350	33	305	600	850	7
SL182956	280	380	60	920	1740	800	19.7
SL183056	280	420	106	1660	2700	800	48
SL181860	300	380	38	375	730	800	10
SL182960	300	420	72	1180	2230	750	31.2
SL183060	300	460	118	2040	3350	700	66.6
SL181864	320	400	38	385	780	750	10.6
SL182964	320	440	72	1220	2360	700	32.9

Bearings NO.	d	D	B	Cr	Cor	Limiting speed	weight
	mm	mm	mm	kN	kN	rpm	kg
SL183064	320	480	121	2090	3500	650	71.7
SL181868	340	420	38	395	820	700	11.2
SL182968	340	460	72	1260	2500	700	34.7
SL183068	340	520	133	2490	4150	600	95.8
SL181872	360	440	38	410	870	650	11.7
SL182972	360	480	723	290	2650	650	36.4
SL183072	360	540	134	2550	4350	550	101
SL181876	380	480	46	570	1150	600	19.2
SL182976	380	520	82	1670	3300	600	52.1
SL183076	380	560	135	2650	4550	550	106
SL181880	400	500	46	590	1220	600	20
SL182980	400	540	82	1720	3500	550	54.3
SL183080	400	600	148	3100	5500	500	140
SL181884	420	520	46	600	1260	550	20.9
SL182984	420	560	82	1750	3600	550	56.9
SL181888	440	540	46	610	1320	550	21.8
SL182988	440	600	95	2130	4200	500	78.1
SL181892	460	580	56	790	1660	500	33.9
SL182992	460	620	95	2160	4350	500	81.1
SL181896	480	600	56	800	1720	500	35.2
SL182996	480	650	100	2430	4900	480	94.7
SL1818/500	500	620	56	820	1810	480	36.5
SL1829/500	500	670	100	2460	5100	460	98.3